



Product Data Sheet

Part # 33101

Fuel System Decarbonizer

Soltec™ Fuel System Decarbonizer is a concentrated detergent designed to penetrate and dissolve harmful deposits found on intake valves and combustion chambers. **Exhaust emissions can be lowered and driveability improved through deposit removal.** Soltec™ Fuel System Decarbonizer uses an alcohol-free formula and can be used in any fuel-injected gasoline engine.

- Removes gum and varnish from intake valves.
- Decarbonizes intake valves and combustion chambers.
- Helps lower exhaust emissions.
- Alcohol-free.
- Will not harm catalytic converters, seals or oxygen sensors.



Application:

For best results, engine should be at normal operating temperature. Eye protection should be worn.

1. Pour Soltec™ Fuel System Decarbonizer into a **Soltec™ Universal Induction Tool #72175**. Connect the tip of the outlet hose to the ported vacuum source as close to the throttle body as possible. Run engine from idle to 2000 RPM and set meter valve to empty bottle in approximately eight to ten minutes. After product has been completely evacuated, shut off engine. Reconnect vacuum hose. Let vehicle sit approximately five to ten minutes. Drive vehicle for a few minutes to remove any residue.

Specifications:

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Brown
Odor	-	Solvent
Specific Gravity @ 60°F (g/ml)	D1298	0.82
Density, U.S. (lbs/gal) @ 60°F	D1250	6.82
Boiling Point (°F)	-	>300
Flash Point (°F) PMCC	D93	>100
%VOC	-	90

Packaging: Fill: 11 Oz Case Quantity: 24 bottles Case Weight: 18 lbs