



Product Data Sheet

Part # 50201

Green Power Steering Solution

Soltec™ Green Power Steering Solution is a fully synthetic fortified power-steering fluid blend that is used in conjunction with the **Soltec™ Power-Steering Fluid Exchanger**. The formulation utilizes polyalphaolefins to ensure outstanding oxidation stability and excellent low temperature performance and shear stability. Due, in part, to its ant-foaming characteristics, the product provides excellent detergency, wear protection, rust inhibition, and seal protection. **Soltec™ Green Power Steering Solution** is suitable for use in Mercedes and BMW vehicles where high quality synthetic hydraulic fluids are required.

- Outstanding cold weather performance.
- Highly resistant to breakdown due to shearing and load (Based on 40 min. Sonic Shear test)
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Superb oxidation stability.



Application:

Soltec™ Green Power Steering Solution should be used with a **Soltec™ Power-Steering Fluid Exchanger**. 1. Follow **Soltec™ Power-Steering Fluid Exchanger** instructions to perform the exchange process. 2. Dispose of the used fluid in accordance with local and federal regulations.

Specifications:

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Green
Odor	-	Petroleum
Specific Gravity @ 60°F (g/ml)	D1298	0.83
Density, U.S. (lbs/gal) @ 60°F	D1250	6.9
Viscosity, cSt @ 100°C	D445	~7
Viscosity, cSt @ 40°C	D445	27
Viscosity Index	D2270	200
Brookfield Viscosity cP @ -40°C	D2983	<3500
Boiling Point (°F)	-	>400
Phosphorus Content, ppm	D5185	150
Zinc Content, ppm	D5185	None

Packaging: Fill: 64 Oz Case Quantity: 6 bottles Case Weight: 26 lbs