



Product Data Sheet

Part # 20001

Cooling Sytem Flush

Soltec™ **Cooling System Flush** is a powerful, convenient, one-step radiator and cooling-system cleaner. It is formulated to quickly breakdown and suspend rust, scale and sediment. This non-acid-base product needs no neutralizer and is compatible with plastic and aluminum.

- Non-acid
- Requires no neutralizer
- Highly effective at removing scale and sediment from system surfaces.
- Can be used on radiator plastic and aluminum components.



Application:

Allow system to cool before removing radiator cap. 1) Remove radiator cap. 2) Pour Fast Flush into radiator. 3) Replace radiator cap. 4) Run engine at operating temperature for ten to fifteen minutes. 5) Flush system with a **MOC® Coolant Exchanger Machine**. Refer to the machine's instructions for additional details and information.

Specifications:

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Colorless
Odor	-	Neutral
pH	D1287	7.2
Specific Gravity @ 60°F (g/ml)	D1298	1.05
Density, U.S. (lbs/gal) @ 60°F	D1250	8.78
Boiling Point (°F)	-	>212

Packaging: Fill: 8 Oz Case Quantity: 24 bottles Case Weight: 16 lbs