

PREMIUM SYNTHETIC ATF-LV

AUTOMOTIVE ADDITIVES & LUBRICANTS - #17613

OUTSTANDING FEATURES

- Highly resistant to shearing, oxidation and thermal breakdown.
- Provides excellent flow properties at low temperatures and film protection at high temperatures.
- Outstanding anti-wear properties to protect transmission parts.
- Optimizes Inventory by eliminating the need to stock different types/brands of ATF.
- Conditions seals and helps prevent leaks.

DESCRIPTION

A special blend of full synthetic base oils combined with a multi-functional additive system that provides superior anti-wear protection and performance in virtually all types of passenger and commercial automatic transmissions that require newer "low viscosity" fluid. It offers excellent high & low temperature fluidity, shear stability, seal protection and oxidation resistance. This premium formula may be used in place of synthetic fluids required or specified by a wide range of OEMs, including those used for extended drain and severe duty intervals. This product is designed to be used in conjunction with the **SOLTEC® ATF Fluid Exchanger #95900 OR 94880 and ATF Cleaner/Supplement Kit #17502.**

APPLICATION

Use in automatic transmissions according to equipment manufacturer's recommendations.
DO NOT use in transmissions that require CVT or Type F fluids.

SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear
Color	-	Red
Density (g/mL)	D4052	0.83
Density, U.S. (lbs/gal), calculated	-	6.93
Viscosity @ 100°C, cSt	D445	~6
Brookfield Viscosity @ -40°C, cPs	D2983	<5,000

PACKAGING

Fill: 1 gal.	Case Quantity: 4	Case Weight: 31.0 lbs.
Fill: 3 gal.	Case Quantity: 2	Case Weight: 45.0 lbs.