

FUEL SYSTEM DECARBONIZER

AUTOMOTIVE ADDITIVES - #33101



OUTSTANDING FEATURES

- Removes gum and varnish from intake valves.
- Removes fuel deposits from intake valves and combustion chambers.
- Helps lower harmful exhaust emissions.
- Alcohol-free.
- Compatible with catalytic converters, seals or oxygen sensors.
- Can also be used with EDR Machine #73520

DESCRIPTION

A concentrated detergent designed to penetrate and dissolve harmful deposits found on intake valves and combustion chambers. Exhaust emissions can be lowered, and drivability improved through deposit removal. Soltec Fuel System Decarbonizer uses an alcohol-free formula and can be used in any fuel-injected gasoline engine.

APPLICATION

For best results, engine should be at normal operating temperature. Eye protection should be worn. 1) Pour product into KDI321 Induction applicator (make sure flow adjustment is closed). 2) Attach tapered end tip of outlet hose to an intake vacuum source. 3) Start engine and set idle at approximately 1500 rpm. 4) Open flow-adjustment valve slowly to allow product to flow into vacuum hose. 5) Set flow to seeing fast drops through the applicator dripper so complete evacuation of the liquid takes approximately 15 minutes. 6) Once bottle is completely emptied, shut off engine and reattach vacuum line to original location. 7) Drive vehicle for 5 minutes to remove residual product.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Brown
Color	-	Brown
Odor	-	Solvent
Density (g/mL)	D4052	0.81
Density, U.S. (lbs/gal), calculated	-	6.76
Flash Point (°F), PMCC	D93	112
Boiling Point (°F), based on components	-	≥284
% VOC	-	90.9

PACKAGING

Fill: 12 oz.

Case Quantity: 24

Case Weight: 19 lbs.