

OIL SYSTEM CLEANER

AUTOMOTIVE ADDITIVES & LUBRICANTS - #43001



OUTSTANDING FEATURES

- Contains an anti-friction additive to help prevent dry starts.
- Helps remove harmful deposits and contaminants.
- Helps clean valve lifters, ring lands and rocker arms.
- Helps reduce engine blow-by.
- Improves fluid circulation.
- Cleans sludge, gum and varnish.

DESCRIPTION

Soltec™ Oil System Cleaner is a dispersant-based cleaning solution that removes accumulated deposits from various oil systems on a vehicle. When used in an engine prior to an oil change, this product removes deposits from lifters, rings, rocker arms and other internal components.

APPLICATION

Make sure oil is at proper level and engine is at operating temperature. 1.) Before performing an oil-and-filter change, add Oil System Cleaner to crankcase. Let car run at idle for 5-10 minutes. Do not rev engine or drive car. 2.) Drain oil and perform an oil-and-filter change according to manufacturer's recommendations.

SPECIFICATIONS

<u>Test</u>	<u>ASTM Method</u>	<u>Typical Results</u>
Appearance	-	Clear & Bright
Color	-	Light Straw
Odor	-	Solvent
Specific Gravity @ 60°F (g/ml)	D1298	0.83
Density, U.S. (lbs/gal) @ 60°F	D1250	6.92
Viscosity, cSt @ 100°C	D445	~1
Boiling Point (°F)	-	>374
Flash Point (°F) PMCC	D93	>167

PACKAGING

Fill: 8 Oz

Case Quantity: 24 Bottles

Case Weight: 14 lbs.