



# POWER STEERING SERVICE SOLUTION - RED

AUTOMOTIVE ADDITIVES & LUBRICANTS - #50101

## OUTSTANDING FEATURES

- Reduces friction that can wear out the pump, valves, and gears.
- Conditions seals and hoses to help prevent cracks and leaks.
- Helps extend system life by reducing wear on internal components.
- Helps reduce squeals and chatter due to foaming.
- Outstanding cold weather performance.

## DESCRIPTION

A fortified power-steering fluid blend that is used in conjunction with a Soltec® Power-Steering Fluid Exchanger. The formulation utilizes a high-quality base fluid which ensures increased oxidation stability and outstanding low temperature performance. The combination of this base oil with a top-quality viscosity modifier ensures excellent resistance to breakdown due to excessive shearing and pressure in power-steering systems. The solution also contains additional components which provide detergency, wear protection, rust inhibition, seal protection and anti-foaming characteristics. The formula meets O.E.M. Power Steering fluid performance requirements for Ford, GM, Chrysler, and Nissan. **NOTE:** Can be packaged and sold in combination with **SOLTEC® Power-Steering Fluid Treatment #52001 (2-Part Kit #54102)**.

## APPLICATION

**SOLTEC®** Power-Steering Service Solution-Red #50101 should only be used with a **SOLTEC®** Power-Steering Fluid Exchanger. 1. Follow the **SOLTEC®** Power-Steering Fluid Exchanger instructions to perform the exchange process. 2. Dispose of used fluid in accordance with local, state, and federal regulations.

## SPECIFICATIONS

Test	ASTM Method	Typical Results
Appearance	-	Clear
Color	-	Dark Red
Odor	-	Bland
Specific Gravity @ 68°F	D1298	.85
Density, U.S. (lbs/gal) @ 68°F	D1250	7.1
Viscosity, cSt @ 100°C	D445	~7
Viscosity, cSt @ 40°C	D445	~35
Viscosity Index	D2270	146
Boiling Point (°F)	-	> 400
Flash Point (°F) (based on components)	-	> 248

## PACKAGING

**Fill:** 64 oz.

**Case Quantity:** 4

**Case Weight:** 17 lbs.